

# MG 8000 SSK (Welfare)

## Welfare Cabin Ready 8kVA Diesel Generator

When looking for a robust, reliable, good quality 8kVA welfare diesel generator look no further than our MG 8000 SSK (Welfare).

**Optional Extras**



Remote Start / Stop



Remote Start / Stop + timer control

**Water Cooled  
Extra Super Silent**



### Features

- 8kVA (230v only)
- Linz alternator
- Kubota diesel engine (3000 rpm)
- Exclusive MHM engine protection shutdown system
- Welfare cabin ready

### Benefits

- Plenty of power to meet the demands of a medium standard welfare cabin
- Heavy duty and proven reliability
- World class performance and watercooled
- In the case of low fuel, low oil pressure, high engine temp. and battery charge failure
- Easy fit plug and play cabin installation

### Specifications

#### Performance

|                                 |      |
|---------------------------------|------|
| Alternator                      | Linz |
| Single Phase Power - kVA (110v) | N/A  |
| Single Phase Power - kVA (230v) | 8    |

|                                |     |
|--------------------------------|-----|
| Three Phase Power - kVA (400v) | N/A |
| Noise Level LWA=89 dBA@7m=64   |     |
| Insulation Class               | H   |
| Mechanical Protection - IP     | 23  |

#### Engine

|                     |        |
|---------------------|--------|
| Make                | Kubota |
| Type                | D722E  |
| Fuel                | Diesel |
| Number of Cylinders | 3      |
| Power - HP          | 17     |

|                                     |          |
|-------------------------------------|----------|
| Engine Speed - rpm                  | 3000     |
| Cooling                             | Water    |
| Fuel Consumption - Litres/hour      | 2.4      |
| Fuel Tank Capacity - litres         | 30       |
| 75% Average Operating Hours - hours | 12.5     |
| Starting System                     | Electric |

#### Dimensions (Machine only)

|                  |                |
|------------------|----------------|
| Length - 1280 mm | Width - 710 mm |
|------------------|----------------|

|                 |                 |
|-----------------|-----------------|
| Height - 880 mm | Weight - 300 Kg |
|-----------------|-----------------|

#### Socket Configuration

|                       | 3ph (400V) |     | 1ph (230V) |     | 1ph (110V) |     |
|-----------------------|------------|-----|------------|-----|------------|-----|
|                       | 32A        | 16A | 32A        | 16A | 32A        | 16A |
| MG 8000 SSK (Welfare) | -          | -   | 1          | 2   | -          | -   |

#### Hard Wire Facility

|                       | 3ph (400V) | 1ph (230V) | 1ph (110V) |
|-----------------------|------------|------------|------------|
| MG 8000 SSK (Welfare) | -          | ✓          | -          |

