

MGTP 60 USKH-5

Event Ready 60kVA Diesel Generator

**HVO
FUEL
APPROVED**

**EVENT
READY
SPECIFICATION**

When looking for a robust, reliable, good quality ultra silenced 60kVA generator, our MGTP 60 USKH-5 has everything the event market requires.

Optional
extras:



Road-tow
Kit



GPS Telemetry
Tracker



Bund Alarm

Features

60kVA 3ph (400V)

Leroy-Somer alternator

Kohler diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil)
fuel approved

Exclusive MHM-Gen engine
protection shutdown system

3 way fuel valve

12V battery isolator switch

Emergency stop button

Central lifting eye and fork pockets

Variable RCD

ELR bypass switch
(activated by key only)

Fully bundled base (110%)

Engine oil drain pump

Benefits

Plenty of power to meet the demands of
medium to large event hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel,
HVO or a mixture of both fuels

In the case of low fuel, low oil pressure, high
engine temp and battery charge failure

Easy connectivity to an external fuel tank

Reduces flat battery breakdowns

A must on any UK site

Flexible and safe lifting on site

Flexible protection

Turn off ELR to avoid nuisance tripping
when powering electrical motor, or other
similar equipment

To retain all spilt fluids

Reducing service time



**ULTRA
SILENCED**
80LWA /
55 dBA@7m

**Stage 5
Engine**



**LOMBARDINI
KOHLER**
2 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Leroy-Somer	Three Phase Power (400V)	60kVA/ 48kW
Single Phase Power (110V)	N/A	Noise Level	LWA=80 dBA@7m=55
Single Phase Power (230V)	20kVA/ 16kW	Insulation Class	N/A
		Mechanical Protection - IP	23

Engine

Make	Kohler	Fuel Consumption @ 75% Load (Litres/hour)	11.4
Type	KD13404TCR CAC (Stage 5)	Fuel Tank Capacity (Litres)	300
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
		@ 100%	19 @ 75% 26
Number of Cylinders	4	@ 50%	38 @ 25% 59
Power (HP)	TBA	CO2 Per Hour @ 75% Load	29.8 kg
Engine Speed (RPM)	1500	Control Panel	Deepsea 7310 c/w two wire Auto Start/ Stop facility
Cooling	Water		

Dimensions (Machine only)

Length: 2600 mm	Width: 1130 mm	Height: 1800 mm
Dry Weight (No Fuel): 1900 kg	Wet Weight (Fuel Full): 2145 kg	

Dimensions (With road-tow kit)

Length: TBA mm	Width: TBA mm	Height: TBA mm
Dry Weight (No Fuel): TBA kg	Wet Weight (Fuel Full): TBA kg	

Socket Configuration	3ph (400V)			1ph (230V)	
	125A	63A	16A	32A	16A
MGTP 60 USKH-5	1	1	1	4	2
Hard wire facility	3ph (400V)			1ph (230V)	
	MGTP 60 USKH-5				
	✓			✓	

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

