

ROAD-TOW PRESSURE WASHER BOWSER 1125-D

1125 litre/ 250 gallon road-towable pressure washer bowser suitable for general washing and cleaning on and off site

When looking for a robust, reliable, good quality road-tow water washer bowser, look no further than our MHM Road-Tow Pressure Washer Bowser 1125-D.



Diesel

TANK & CHASSISFeatures

1125 litre capacity

Internal anti-surge baffle

22 inch lockable top access cover

Inner sealed and vented lid

Protective galvanised base and durable corrosion free polyethylene inner and outer tank secured by 2 x stainless steel straps

Lifting points & fork pockets

Complete on road-tow chassis

Benefits

Can be safely transported full of water and enough storage for most construction site applications

Additional stability for transport

Secure and simple refill access

Extra protection

Robust, long lasting & ready for work in any environment

For flexible & safe loading & unloading

Single axle, suspension, brakes, mudguard & rear lights – *suitable for UK highway use*



PRESSURE WASHERFeatures

3000 PSI/ 200 Bar

Interpump water pump

Return to tank unloader valve

1450rpm gearbox drive

Yanmar diesel engine

Strong protective metal frame

Hand lance holder & hose storage

Detergent/chemical feed-line c/w strainer filter

Benefits

Plenty of pressure for most site washing application

Heavy duty and proven reliability

Maximum protection for a rental environment

Reduced speed for cooler running & improved longevity

Power, reliability & robust strength

Great protection for a rental & construction environment

Performance

For safe and secure transport & storage

Simple connectivity for easy use of various cleaning products

Optional extras:





3000 PSI / 200 Ran













Specification

Engine	
Make	Yanmar
Туре	L100
Fuel Diesel / HVO (HVO = BS EN 15940	:2016 Only)
Number of Cylinders	1
Power (HP)	10

Engine Speed (RPM)	3250
Cooling	Air
Fuel Consumption @ 75% Load (Litres/hour)	1.5
Fuel Tank Capacity (Litres)	5.5
Average Runtime (Hours) @ 75% Load	3.6
Starting System E	lectric

Periorilai	ice		Max Liggznig	300	JU F31/ 200 Dai		
Pump Brand	Inter	rpump	Max Flow 1	5 Ltr per Min	/ 4 Gal per Min		
Pump Model	Piston Type/\	WS201	Hose Length		10m		
Drive	Gearbox @14	50rpm	Noise Level	LWA=99	dBa@7m=74		
Technical			Design Appro	oval	UK Standard		
Capacity (full)	1125 Litre / 250	Gallon	Bund Material (thickness) 7mm		7mm		
Fluid	Site Wate	er Only	Inner Tank (thickness) 7mm				
Dimensions (With Road-Tow Kit)							
Length: 3500 m	nm	Width: 15	50 mm Height: 1400 mm				
Dry Weight (No	Water): 375 kg		Wet	Weight (Wate	r Full): 1500 kg		

For more details call MHM TODAY on 0808 168 9099

Email sales@mhmplant.com or visit us at www.mhmplant.com





