

FUEL

BABY-LITE (LED-4)

Lighting Tower complete with

Extra Super Silent 6kVA Diesel Generator

When looking for a portable, easy to manage and highly versatile lighting solution, look no further than our MHM Lightower Baby-Lite (LED-4).







Features

LIGHTING TOWER

4 x 200W LED 360° swivel & tilt lighting head (230V or 110V power required)

4m vertical stainless steel vertical mast

Front, side & rear fork pockets

Generator can be removed in under 10 minutes

Complete on trolley kit, folding handles + 2 x fully adjustable stabiliser legs

GENERATOR

6kVA (230V/110V) AC generator power

Linz alternator

Yanmar diesel engine

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Central lifting eye

Fully bunded base

Extra super silent canopy

Benefits

LIGHTING TOWER

2.300m² of illuminated light coverage

For quick and simple erection

For easy lifting on site

Allowing the use of either the lighting rig or generator separately

For easy portability and set up

GENERATOR

Plenty of power to run the lighting head plus small tools on site

Heavy duty and proven reliability

Electric start, power, reliability & robust strength

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

For extra safe on site lifting

To retain all spilt fluids

Reduced noise level














BABY-LITE (LED-4) C/W Extra Super Silent 6kVA Diesel Generator









Standard load delivery

Specification

Performance		Three Phase Power (400v)	N/A
Alternator	Linz	Noise Level LWA=84 dBa@	҈97m=59
Single Phase Power (110V)	6kVA/ 4.8kW	Insulation Class	Н
Single Phase Power (230V)	6kVA/ 4.8kW	Mechanical Protection - IP	23
Engine			
Make	Yanmar	Cooling	Air
Туре	L100AE	Fuel Consumption — Litres/hour	0.9
Fuel Diesel / HVO (HVO = BS E	N 15940:2016 Only)	Fuel Tank Capacity — Litres	25
Number of Cylinders	1	Average Runtime 'All Lights On'	27
Power — HP	10	CO2 Output Per Hour 'All Lights On'	2.36 kg
Engine Speed — RPM	3000	Starting System	Electric
Lighting		Max Mast Height	4m
Light Coverage	2,300m ²	Mast Type	Manual
Lighting Head	4 x 200W LED	Certified Wind Stability 110kph	/ 70mph

Length: 1080 mm Wid	dth: 590 mm Maxir	num Load Weight:	275 kg				
Dimensions (Storag	ge mode: handles folded in	, stabilisers up & mas	st down)				
Length: 1470 mm	Width: 865 mm	Не	Height: 1900 mm				
Dimensions (Operating mode: handles folded out, stabilisers down & mast up)							
Length: 1870 mm	Width: 865 mm	Н	Height: 4000 mm				
Dry Weight (No Fuel): 416	kg	Wet Weight (F	uel Full): 442 kg				

Socket	1ph (230V)		1ph (110V)	
Configuration	32A	16A	32A	16A
Generator	1	1	1	2

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com





