

# MG 3000 SD-5/ES-RT

3kVA Railtrack Approved Diesel Generator

When looking for robust, reliable, good quality 3kVA Railtrack Approved diesel generator, look no further than our MG 3000 SD-5/ES-RT.



### Features Benefits

Railtrack approved

3kVA (110V) CTE (55V-0-55V)

Linz alternator

Kohler/Lombardini diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Complete with trolley kit + folding handles

Only 78kg

Complete with electric starting system

Trackside ready

Plenty of power to run a variety of tools on site

Heavy duty and proven reliability

Electric start, power, reliability and robust strength

Suitable to run off either diesel, HVO or a mixture of both fuels

For nice and easy manoeuvrability and storage

Lightweight design

Effort-free start up



## Specification

### **Performance**

Alternator	Linz
Single Phase Power (110V)	3kVA/ 2.4kW
Single Phase Power (230V)	N/A

Noise Level	LWA=95	dBa@7m=70
Insulation Class		Н
Mechanical Protec	tion - IP	23

#### **Engine**

Make	Kohler/ Lombardini	
Туре	15LD350 (Stage 5)	
Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only)		
Number of Cylinders	1	
Power (HP)	6.5	
Engine Speed (RPM)	3000	

Cooling	Air
Fuel Consumption @ 75% Load (Litres/hou	r) <b>0.7</b>
Fuel Tank Capacity (Litres)	13
Average Runtime@ 75% Load (Hours)	17
CO2 Output Per Hour @ 75% Load	1.83kg
Starting System	Electric

### **Dimensions** (Machine only)

Length: /65 mm	Width: 525 mm		ght: 590 mm	
Dry Weight (No Fuel): <b>78</b> kg		Wet Weight (Fuel Full): 91 kg		
<b>Dimensions</b> (Trolley kit with handles folded out)				
Length: 1460 mm	Width: 750 mm	Hei	ght: <b>725</b> mm	
Dry Weight (No Fuel): 83 kg	Wet Weight (Fuel Full): <b>96</b> kg			
	_			
<b>Socket Configuration</b>		1ph (110V)		
Socket Configuration	224		164	

Socket Configuration	1ph (110V)	
	32A	16A
MG 3000 SD-5/ES-RT	1	2

For more details call MHM TODAY

on **0808 168 9099** 

Email sales@mhmplant.com or visit us at www.mhmplant.com





2 Year Engine arranty (Limited)







