

MG 4000 SD-5/ES-RT

4kVA Railtrack Approved Diesel Generator

When looking for robust, reliable, good quality 4kVA Railtrack Approved diesel generator, look no further than our MG 4000 SD-5/ES-RT.



Features

Railtrack approved
4kVA (110V) CTE (55V-0-55V)
Linz alternator
Kohler/ Lombardini diesel engine (Stage 5)
HVO (Hydrotreated Vegetable Oil) fuel approved
Complete with trolley kit + folding handles
Only 79kg
Complete with electric starting system

Benefits

Trackside ready
Plenty of power to run a variety of tools on site
Heavy duty and proven reliability
Electric start, power, reliability and robust strength
Suitable to run off either diesel, HVO or a mixture of both fuels
For nice and easy manoeuvrability and storage
Lightweight design
Effort-free start up

Electric
start



Stage 5
Engine



**LOMBARDINI
KOHLER**
2 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Linz	Noise Level	LWA=95 dBa@7m=70
Single Phase Power (110V)	4kVA/ 3.2kW	Insulation Class	H
Single Phase Power (230V)	N/A	Mechanical Protection - IP	23

Engine

Make	Kohler/ Lombardini	Cooling	Air
Type	15LD350 (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)	1
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	13
Number of Cylinders	1	Average Runtime@ 75% Load (Hours)	13
Power (HP)	6.5	CO ₂ Output Per Hour @ 75% Load	2.62kg
Engine Speed (RPM)	3000	Starting System	Electric

Dimensions (Machine only)

Length: 765 mm	Width: 525 mm	Height: 590 mm
Dry Weight (No Fuel): 79 kg	Wet Weight (Fuel Full): 92 kg	

Dimensions (Trolley kit with handles folded out)

Length: 1460 mm	Width: 750 mm	Height: 725 mm
Dry Weight (No Fuel): 84 kg	Wet Weight (Fuel Full): 97 kg	

Socket Configuration

	1ph (110V)	
	32A	16A
MG 4000 SD-5/ES-RT	1	2

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

