

MG 10000 SSK-3PH

Ready to Rent 10kVA Diesel Generator

When looking for a robust, reliable, good quality 10kVA diesel generator, look no further than our MG 10000 SSK-3ph

FUEL



Optional extras:





Features

10kVA (400V – 3ph) AC Aux Power

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

Benefits

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage

Water Cooled Extra Super Silent



Kuboto

2 Year Engine
Warranty (Limited)



Specification

Performance

Linz
N/A
3.3kVA/ 2.6kW

Noise Level	LWA=89	dBa@7m=64
Insulation Class		Н
Mechanical Protection	on - IP	23

Engine

Make	Kubota
Туре	D722E (Stage 3)
Fuel Diesel / HVO (HVO	= BS EN 15940:2016 Only)
Number of Cylinders	3
Power (HP)	17
Engine Speed (RPM)	3000
Cooling	Water

Fuel Consumption	ır) 2.8		
Fuel Tank Capacity	40		
Average Runtime (Hours)			
@ 100% Load	11	@ 75% Load	14
@ 50% Load	22	@ 25% Load	44
CO2 Per Hour @ 75% Load 7.			7.34kg
Starting System Deepsea 3110 c/w two w Auto Start/ Stop facil			

Dimensions (Machine only)

Length: 1220 mm	Width: 670 mm	Height: 840 mm
Dry Weight (No Fuel): 350 kg		Wet Weight (Fuel Full): 381 kg

Dimensions (Trolley kit with handles folded out)

Length: 1635 mm	Width: 940 mm	Height: 980 mm
Dry Weight (No Fuel): 365 kg		Wet Weight (Fuel Full): 396 kg

Dimensions (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: 1200 mm
Dry Weight (No Fuel): 485 kg		Wet Weight (Fuel Full): 516 kg

Socket	3ph (400V)		1ph (230V)		
Configuration	32A	16A	32A	16A	
MG 10000 SSK-3ph	1	-	-	1	
Hard wire facility	3ph (400V)		1ph (2	230 V)	
MG 10000 SSK-3ph	V		0000 SSK-3ph		

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com











