#### Ready To Rent Diesel Generators //



H O

EVEL

APPROVED

Water Cooled

Extra Super

**MG 10000 SSK-ECO** Ready to Rent 10kVA Eco Diesel Generator

### When looking for a robust, reliable, good quality 10kVA diesel generator, look no further than our MG 10000 SSK-ECO.

Optional extras: Road-tow OB GPS Telemetry Kit Tracker

### Features

Eco Auto Start/Stop mode allows the generator to automatically start & stop according to generator power demand

ceording to generator porter demand	
0kVA (230V / 110V) IC Aux Power	
inz alternator	
ubota diesel engine (Stage 3)	
IVO (Hydrotreated Vegetable Oil) fuel pproved	
xclusive MHM engine protection hutdown system	
mergency stop button	
entral lifting eye and ront & side fork pockets	
ully bunded base (110%)	
omplete with trolley kit folding handles	

# Benefits

The Eco system reduces noise, fuel consumption and carbon emmission

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage

## Specification

#### Performance

	nz	Noise Level	LWA=89 dBa	@7m=64
Single Phase Power (110V) 10kVA/ 8k	W	Insulation Cl	ass	Н
Single Phase Power (230V) 10kVA/ 8k	W	Mechanical	Protection – IP	23
Engine	Fu	el Consumptior	n @ 75% Load (Litres/ho	our) <b>2.8</b>
Make Kubota	Fu	el Tank Capacity	y (Litres)	40
Type D722E (Stage 3)	Av	Average Runtime (Hours)		
Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only)	@	100% Load	11 @ 75% Load	14
Number of Cylinders 3	@	50% Load	<b>22</b> @ 25% Load	44
Power (HP) 17	CC	)2 Per Hour @ 7	5% Load	7.34kg
Engine Speed (RPM) 3000	C+	arting System		Koy Start
Cooling Water		Starting System K		Key Start

#### Stage 3 Engine Year Warrant

Kubota 2 Year Engine Warranty (Limited)

SPECIFICATION

START/STOP

#### **Dimensions** (Machine only)

Length: <b>1220</b> mm	Width: <b>670</b> mm	Height: 840 mm
Dry Weight (No Fuel): <b>350</b> kg		Wet Weight (Fuel Full): 381 kg

Dimensions (Trolley kit with handles folded out)				
Length: 1635 mm	Width: <b>940</b> mm	Height: <b>980</b> mm		
Dry Weight (No Fuel): 365 kg		Wet Weight (Fuel Full): <b>396</b> kg		

Dimensions	(With road-tow kit)	

Designed in the UK,

built in Italy

Length: <b>2650</b> mm	Width: <b>1300</b> mm	Height: <b>1200</b> mm	
Dry Weight (No Fuel): <b>485</b> kg		Wet Weight (Fuel Full): <b>516</b> kg	

Socket	1ph (230V)		1ph (110V)	
Configuration	32A	16A	32A	16A
MG 10000 SSK-ECO	1	1	2	1
Hard wire facility	1ph (230V)		1ph (110V)	
MG 10000 SSK-ECO	v		V	

## For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.

(in) (0