

MG 15000 SSY-5-MV

Ready to Rent 15kVA Diesel Generator

Multi Voltage

400V 230V 110V

When looking for a robust, reliable, good quality 15kVA rental-friendly generator, our MG 15000 SSY-5-MV has everything the market requires.

Optional extras:



Road-tow Kit



Trolley kit



GPS Telemetry Tracker

Water Cooled
Extra Super Silent

HVO FUEL APPROVED

READY TO RENT SPECIFICATION

Features

15kVA Multi-Voltage
AC Aux Power

Linz (AVR) alternator

Yanmar diesel engine
(Stage 5)

HVO (Hydrotreated Vegetable Oil)
fuel approved

Exclusive MHM engine protection
shutdown system

12V battery isolator switch

Emergency stop button

Central lifting eye and fork pockets

Fully bunded base (110%)

Engine oil drain pump

Benefits

Hugely versatile with a massive
advantage in the rental market

Heavy duty and proven reliability

World class performance
and watercooled

Suitable to run off either diesel, HVO
or a mixture of both fuels

In the case of low fuel, low oil
pressure and battery charge failure

Reduces flat battery breakdowns

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

Reducing service time



Stage 5 Engine



YANMAR
3 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Linz (AVR)	Three Phase Power (400V)	15kVA/ 12kW
Single Phase Power (110V)	12kVA/ 9.6kW	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	15kVA/ 12kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	Yanmar	Fuel Consumption @ 75% Load (Litres/hour)	3.7
Type	TBA (Stage 5)	Fuel Tank Capacity (Litres)	40
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	3	@ 100% Load	7
Power (HP)	26	@ 75% Load	10
Engine Speed (RPM)	3000	@ 50% Load	10
Cooling	Water	@ 25% Load	38
		CO ₂ Per Hour @ 75% Load (kg)	9.69
		Starting System	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1440 mm	Width: 810 mm	Height: 890 mm
Dry Weight (No Fuel): 425 kg		Wet Weight (Fuel Full): 465 kg

Dimensions (Trolley kit with handles folded out)

Length: 2002 mm	Width: 990 mm	Height: 1050 mm
Dry Weight (No Fuel): 435 kg		Wet Weight (Fuel Full): 475 kg

Dimensions (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: 1340 mm
Dry Weight (No Fuel): 560 kg		Wet Weight (Fuel Full): 594 kg

Socket Configuration	3ph (400V)		1ph (230V)		1ph (110V)	
	32A	16A	32A	16A	32A	16A
15000 SSY-5-MV	1	-	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
	32A	16A	32A	16A	32A	16A
15000 SSY-5-MV	✓	✓	✓	✓	✓	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



The Preferred Supplier

