

MG 6000 SSK

Ready to Rent 6kVA Diesel Generator

When looking for a robust, reliable, good quality 6kVA diesel generator, look no further than our MG 6000 SSK.



Optional extras:





Water Cooled Extra Super Silent



Year Engine
Warranty (Limited)

Features

6kVA (230V / 110V) AC Aux Power

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

Benefits

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage



Specification

Performance

| 'A/ 4.8kW | Insulat |
|-----------|---------|
| 'A/ 4.8kW | Mecha |
| | |

| Noise Level | LWA=89 | dBa@7m=64 |
|----------------------------|--------|-----------|
| Insulation Class | | Н |
| Mechanical Protection - IP | | 23 |
| | | |

| Engine | |
|-------------------------|--------------------------|
| Make | Kubota |
| Туре | Z482 (Stage 3) |
| Fuel Diesel / HVO (HVO= | = BS EN 15940:2016 Only) |
| Number of Cylinders | 2 |
| Power (HP) | 9.5 |
| Engine Speed (RPM) | 3000 |
| | |

| Cooling | 1 | Water |
|--|------------------------|-------|
| Fuel Consumption @ | 75% Load (Litres/hour) | 1.8 |
| Fuel Tank Capacity (I | Litres) | 40 |
| Average Runtime@ | 75% Load (Hours) | 22 |
| CO2 Output Per Hou | r @ 75% Load 4 | .72kg |
| Starting System Deepsea 3110 c/w two wire Auto Start/ Stop facility | | |

Dimensions (Machine only)

| Length: 1220 mm | Width: 670 mm | Height: 840 mm |
|------------------------------|---------------|--------------------------------|
| Dry Weight (No Fuel): 340 kg | | Wet Weight (Fuel Full): 371 kg |
| | | |

Dimensions (Trolley kit with handles folded out)

| Length: 1635 mm | Width: 940 mm | Height: 980 mm |
|------------------------------|---------------|--------------------------------|
| Dry Weight (No Fuel): 355 kg | | Wet Weight (Fuel Full): 386 kg |

Dimensions (With road-tow kit)

| Length: 2650 mm | Width: 1300 mm | Height: 1200 mm |
|------------------------------|----------------|--------------------------------|
| Dry Weight (No Fuel): 475 kg | | Wet Weight (Fuel Full): 506 kg |

| Socket | 1ph (230V) | | 1ph (110V) | |
|--------------------|------------|-----|------------|-------|
| Configuration | 32A | 16A | 32A | 16A |
| MG 6000 SSK | 1 | 1 | 1 | 2 |
| Hard wire facility | 1ph (230V) | | 1ph (| 110V) |
| MG 6000 SSK | ✓ | | v | / |

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com











