

# MGTP 100 SSF

Ready to Rent 100kVA Diesel Generator



When looking for a robust, reliable, good quality 100kVA rental-friendly generator, our MGTP 100 SSF has everything the hire market requires.

Optional extras:





### **Features**

100kVA 3ph AC Aux Power (400V)

Linz alternator

FPT (Iveco) diesel engine (Stage 3A)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM-Gen engine protection shutdown system

3 way fuel valve

12V battery isolator switch

Emergency stop button

Variable RCD

ELR bypass switch (activated by key only)

Central lifting eye and fork pockets

Fully bunded base

Engine oil drain pump

### Benefits

Plenty of power to meet the demands of medium to large generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure, high engine temp and battery charge failure

Easy connectivity to an external fuel tank

Reduces flat battery breakdowns

A must on any UK site

Flexible protection

Turn off the ELR to avoid nusiance tripping when powering electrical motors

Flexible and safe lifting on site

To retain all spilt fluids

Reducing service time









## Specification

### **Performance**

Alternator	Linz (AVR Controlled)		
Single Phase Power (11	10V) N/A		
Single Phase Power (23	33kVA/ 26.4kW		

Three Phase Power (400V) 100kVA/ 8	BUKW
Noise Level LWA=88 dBa@7n	n=63
Insulation Class	Н
Mechanical Protection - IP	23

### **Engine**

Make	FPT (Iveco)
Туре	N45 TE2F (Stage 3A)
Fuel Diesel / HVO	(HVO = BS EN 15940:2016 Only)
Number of Cylinder	s 4
Power (HP)	135
Engine Speed (RPM	1500
Cooling	Water

Taci consumption (2 73 70 Loda (Litres/ noul)				
Fuel Tank Capacity (Litres)				
Average Runtime (Hours)				
@ 100% Load 11 @ 75% Load				
@ 50% Load	20	@ 25% Load	36	
CO2 Per Hour @ 75	% Load	d	48.99kg	
Control Panel Deepsea 7310 c/w two Auto Start/ Stop fa				

Fuel Consumption @ 75% Load (Litres/hour) 18.7

#### **Dimensions** (Machine only)

Length: 2600 mm	Width: 1180 mm	Height: <b>1740</b> mm
Dry Weight (No Fuel): 1690 kg		Wet Weight (Fuel Full): 1940 kg
<b>Dimensions</b> (With road-to	ow kit)	

Length: 4800 mm	Width: 1840 mm	Height: 2250 mm
Dry Weight (No Fuel): 2280 kg		Wet Weight (Fuel Full): 2530 kg

Socket	3ph (400V)			1ph (230V)			
Configuration	125A	63A	32A	16A	32A	16A	
MGTP 100 SSF	1	1	1	-	4	2	
Hard wire facility	3ph (400V)			1	1ph (230V)		
MGTP 100 SSF	V		<b>✓</b>				

For more details call MHM TODAY

on **0808 168 9099** 

Email sales@mhmplant.com or visit us at www.mhmplant.com











