

 Multi Voltage

400V 230V 110V

**MGTP 16 SSY-MV** Ready to Rent 16kVA Diesel Generator

When looking for a robust, reliable, good quality 16kVA rental-friendly generator, our MGTP 16 SSY-MV has everything the hire market requires.

Benefits

Optional extras:

Road-tow On GPS Telemetry Kit Tracker

### Features

16kVA Multi-Voltage AC Aux Power (400V / 230V / 110V)

#### Linz alternator

Yanmar diesel engine (Stage 3A	)
HVO (Hydrotreated Vegetable C fuel approved	Dil)
Exclusive MHM-Gen engine protection shutdown system	
3 way fuel valve	
3 way fuel valve 12V battery isolator switch	

ELR bypass switch (activated by key only) Central lifting eye and fork pockets Fully bunded base (110%) Engine oil drain pump Hugely versatile with a massive advantage in the rental market Heavy duty and proven reliability World class performance and watercooled Suitable to run off either diesel, HVO or a mixture of both fuels In the case of low fuel, low oil pressure, high engine temp and battery charge failure Easy connectivity to an external fuel tank Reduces flat battery breakdowns A must on any UK site Flexible protection Turn off the ELR to avoid nusiance tripping when powering electrical motors Flexible and safe lifting on site To retain all spilt fluids Reducing service time

Three Phase Power (400V) 16kVA/ 12.8kW



ANMAR

3 Year Engine

Warranty (Limited)

## Specification

### Performance

Terrormance			_	THICCT HUSCT	OWCI (		2.0111	
	Alternator Linz	z (AVR Controlle	ed)		Noise Level		LWA=88 dBa@7	′m=63
	Single Phase Power (110V)	16kVA/ 12.8k	W		Insulation Cla	SS		Н
	Single Phase Power (230V)	16kVA/ 12.8k	W		Mechanical P	rotectio	on – IP	23
				_				
	Engine Fuel Consumption @ 75% Load (Litres/hour) 4.2						) 4.2	
	Make	Yanmar	Fu	uel	Tank Capacity	(Litres)		120
			A	Average Runtime (Hours)				
	Fuel <b>Diesel / HVO</b> (HVO = BS EM	15940:2016 Only)	a	9 1(	00% Load	26	@ 75% Load	28
	Number of Cylinders	3	a	9 5(	)% Load	41	@ 25% Load	80
Power (HP) 27			C	CO2 Per Hour @ 75% Load 1				11kg
	Engine Speed (RPM)	1500		o. n.t	val Dan al	Dee	psea 3110 c/w tw	/o wire
Power (HP)27Engine Speed (RPM)1500		Water	0	Control Panel Auto Start/ Stop				facility

Dimensions (Machine only)									
Length: 1850 mm	Width: <b>970</b> mm	l	Height: <b>1520</b> mm						
Dry Weight (No Fuel): 700	Wet Weight	Wet Weight (Fuel Full): 820 kg							
Dimensions (With road-tow kit)									
Length: 3310 mm	Width: <b>1625</b> mr	Height: <b>1950</b> mm							
Dry Weight (No Fuel): 930	kg	Wet Weight (	Fuel Full): <b>1050</b> kg						

Stage **3**A

Engine


Socket	<b>3ph</b> (4	400V)	1ph (2	230V)	1ph (110V)	
Configuration	32A	16A	32A	16A	32A	16A
MGTP 16 SSY-MV	1	-	2	2	3	1
Hard wire facility	3ph (400V)		1ph (2	230V)	1ph (110V)	
MGTP 16 SSY-MV			6	/	~	

Designed in the UK,

built in Italy

# For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com





(in) (0