

APPROVED Multi Voltage

400V <mark>230V</mark> 110V

MGTP 20 SSY-MV Ready to Rent 20kVA Diesel Generator

When looking for a robust, reliable, good quality 20kVA rental-friendly generator, our MGTP 20 SSY-MV has everything the hire market requires.

Optional extras:

GPS Telemetry Tracker Road-tow Kit

Features

20kVA Multi-Voltage AC Aux Power (400V / 230V / 110V)

Linz alternator

Yanmar diesel engine (Stage 3A) HVO (Hydrotreated Vegetable Oil) fuel approved Exclusive MHM-Gen engine protection shutdown system 3 way fuel valve 12V battery isolator switch

Emergency stop button Variable RCD ELR bypass switch (activated by key only) Central lifting eye and fork pockets Fully bunded base (110%) Engine oil drain pump

Benefits Hugely versatile with a massive advantage in the rental market Heavy duty and proven reliability World class performance and watercooled Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure, high engine temp and battery charge failure

Easy connectivity to an external fuel tank Reduces flat battery breakdowns

A must on any UK site Flexible protection

Turn off the ELR to avoid nusiance tripping when powering electrical motors Flexible and safe lifting on site

To retain all spilt fluids Reducing service time

Stage **3**A

Engine



ANMAR

3 Year Engine

Warranty (Limited)

Specification

_					
Р	er	'to	rm	an	10

Performance			Three Phase P	ower	(400V) 20k	VA/ 16kW
Alternator Linz (AVR Controlled)			Noise Level		LWA=88 dBa	@7m=63
Single Phase Power (110V) 20kVA/ 16kW			Insulation Clas	SS		Н
Single Phase Power (230V) 20kVA/ 16kW			Mechanical Protection – IP			23
Engine Fuel Consumption @ 75% Load (Litres/hour) 4.6						our) 4.6
Make Yanmar		Fuel Tank Capacity (Litres)			120	
Type TBA (Stage 3A)			Average Runtime (Hours)			
Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only)			100% Load	21	@ 75% Load	26
Number of Cylinders	4	@ 5	50% Load	43	@ 25% Load	86
Power (HP)	27	(02	2 Per Hour @ 75% Load		12.05kg	
Engine Speed (RPM)	1500	Con	Control Panel Deepsea 3110 c/w two wi Auto Start/ Stop facili		two wire	
Cooling	Water	COL			op facility	

Dimensions (Machine only)							
Length: 1850 mm	Width: 970 mm	Height: 1520 mm					
Dry Weight (No Fuel): 705 kg	Wet Weight (Fuel Full): 825 kg						
Dimensions (With road-tow kit)							
Length: 3310 mm	Width: 1625 mm	Height: 1950 mm					
Dry Weight (No Fuel): 935 kg	Wet Weight (Fuel Full): 1055 kg						
Socket	3ph (400V)	1ph (230V)	1ph (110V)				

Socket	3ph (400V)		1ph (230V)		1ph (110V)	
Configuration	63A	32A	32A	16A	32A	16A
MGTP 20 SSY-MV	-	1	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
MGTP 20 SSY-MV	 ✓ 		V		~	

For more details call MHM TODAY on 0808 168 9099

Email sales@mhmplant.com or visit us at www.mhmplant.com

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.

