

MGTP 25 SSK-MV

Ready to Rent 25kVA Diesel Generator

**Multi
Voltage**
400V 230V 110V

When looking for a robust, reliable, good quality 25kVA rental-friendly generator, our MGTP 25 SSK-MV has everything the hire market requires.



Optional
extras:



Road-tow
Kit



GPS Telemetry
Tracker

Features

25kVA Multi-Voltage AC Aux Power
(400V / 230V / 110V)

Linz alternator

Kubota diesel engine (Stage 3A)

HVO (Hydrotreated Vegetable Oil)
fuel approved

Exclusive MHM-Gen engine
protection shutdown system

3 way fuel valve

12V battery isolator switch

Emergency stop button

Variable RCD

ELR bypass switch
(activated by key only)

Central lifting eye and fork pockets

Fully bunded base (110%)

Engine oil drain pump

Benefits

Hugely versatile with a massive advantage
in the rental market

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO
or a mixture of both fuels

In the case of low fuel, low oil pressure,
high engine temp and battery
charge failure

Easy connectivity to an external fuel tank

Reduces flat battery breakdowns

A must on any UK site

Flexible protection

Turn off the ELR to avoid nuisance tripping
when powering electrical motors

Flexible and safe lifting on site

To retain all spilt fluids

Reducing service time



Stage 3A
Engine



Kubota
2 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Linz (AVR Controlled)	Three Phase Power (400V)	25kVA/ 20kW
Single Phase Power (110V)	25kVA/ 20kW	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	25kVA/ 20kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	Kubota	Fuel Consumption @ 75% Load (Litres/hour)	5
Type	V2203 (Stage 3A)	Fuel Tank Capacity (Litres)	120
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	4	@ 100% Load	19
Power (HP)	27	@ 75% Load	24
Engine Speed (RPM)	1500	@ 50% Load	39
Cooling	Water	@ 25% Load	75
		CO ₂ Per Hour @ 75% Load	13.1kg
		Control Panel	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1850 mm	Width: 970 mm	Height: 1520 mm
Dry Weight (No Fuel): 710 kg	Wet Weight (Fuel Full): 830 kg	

Dimensions (With road-tow kit)

Length: 3310 mm	Width: 1624 mm	Height: 1950 mm
Dry Weight (No Fuel): 940 kg	Wet Weight (Fuel Full): 1060 kg	

Socket Configuration	3ph (400V)		1ph (230V)		1ph (110V)	
	63A	32A	32A	16A	32A	16A
MGTP 25 SSK-MV	-	1	2	2	3	1

Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
	✓	✓	✓	✓	✓	✓
MGTP 25 SSK-MV	✓	✓	✓	✓	✓	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

