Ready To Rent Diesel Generators //



APPROVED

Multi Voltage

400V <mark>230V</mark> 110V

MGTP 25 SSY-MV Ready to Rent 25kVA Diesel Generator

When looking for a robust, reliable, good quality 25kVA rental-friendly generator, our MGTP 25 SSY-MV has everything the hire market requires.

Benefits

Optional extras:

Road-tow On GPS Telemetry Kit Tracker

Features

25kVA Multi-Voltage AC Aux Power (400V / 230V / 110V)

Linz alternator

Yanmar diesel engine (Stage 3A)
HVO (Hydrotreated Vegetable Oil) fuel approved
Exclusive MHM-Gen engine protection shutdown system
3 way fuel valve

12V battery isolator switch Emergency stop button Variable RCD ELR bypass switch (activated by key only) Central lifting eye and fork pockets Fully bunded base (110%) Engine oil drain pump Hugely versatile with a massive advantage in the rental market Heavy duty and proven reliability World class performance and watercooled Suitable to run off either diesel, HVO or a mixture of both fuels In the case of low fuel, low oil pressure, high engine temp and battery charge failure Easy connectivity to an external fuel tank Reduces flat battery breakdowns A must on any UK site Flexible protection Turn off the ELR to avoid nusiance tripping when powering electrical motors Flexible and safe lifting on site To retain all spilt fluids

Three Phase Power (400V) 25kVA/ 20kW

Reducing service time

Specification

Performance

i ci ioi illance			milliocimuse	i owci (201	20101	
Alternator Linz	(AVR Controlled)		Noise Level		LWA=88 dBa	a@7m=63	
Single Phase Power (110V)	ngle Phase Power (110V) 25kVA/ 20kW		Insulation Cla	ass		Н	
Single Phase Power (230V)	25kVA/ 20kW		Mechanical Protection - IP			23	
Engine		Fue	l Consumption	ı @ 75%	Load (Litres/h	our) 5	
Make	Yanmar	Fuel Tank Capacity (Litres)				120	
Type TBA (Stage 3A)			Average Runtime (Hours)				
Fuel Diesel / HVO (HVO = BSEN	15940:2016 Only)	@1	00% Load	19	@ 75% Load	24	
Number of Cylinders	4	@ 5	50% Load	39	@ 25% Load	75	
Power (HP)	27	CO2 Per Hour @ 75% Load			13.1kg		
Engine Speed (RPM)	1500	Car	tral Danal	Dee	psea 3110 c/v	v two wire	
Cooling	Water	COL	Auto Start/ Stop faci		top facility		

3ph (3ph (400V) 63A 32A		1ph (230V) 32A 16A		110V)		
Socket 3ph (400V) 1ph (230V) 1ph (110V)							
DIY Weight (No rue). 940 kg Wel Weight (ruel ruh). 1060 kg							
Width: 1625 mm Height: 1950 mr				950 mm			
ad-tow k	it)						
) kg Wet Weight (Fuel Full): 830 kg							
Wi	dth: 970 r	nm	Height: 1520 mm				
	Wi ad-tow k Wid	Width: 970 r ad-tow kit) Width: 1625	Width: 970 mm Ad-tow kit) Width: 1625 mm Width: Width:	Width: 970 mm Wet Weight ad-tow kit) Width: 1625 mm Wet Weight (Wet Weight (Fuel Full) Width: 1625 mm Wet Weight (Fuel Full):		

Stage **3** A

Engine

	0.511		5211	10/1	5211	Ton
MGTP 25 SSY-MV	-	1	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
MGTP 25 SSY-MV	~		Ŀ	/	V	

Designed in the UK.

built in Italy

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.

(in)

ANMAR

3 Year Engine

Warranty (Limited)