

MGTP 33 SSF

Ready to Rent 33kVA Diesel Generator

When looking for a robust, reliable, good quality 33kVA rental-friendly generator, our MGTP 33 SSF has everything the hire market requires.

Optional extras:



Road-tow Kit



GPS Telemetry Tracker

Features

33kVA 3ph Aux Power

Linz alternator

FPT (Iveco) diesel engine (Stage 3A)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM-Gen engine protection shutdown system

3 way fuel valve

12V battery isolator switch

Emergency stop button

Variable RCD

ELR bypass switch (activated by key only)

Central lifting eye and fork pockets

Fully bunded base (110%)

Engine oil drain pump

Benefits

Plenty of power to meet the demands of small to medium generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure, high engine temp and battery charge failure

Easy connectivity to an external fuel tank

Reduces flat battery breakdowns

A must on any UK site

Flexible protection

Turn off the ELR to avoid nuisance tripping when powering electrical motors

Flexible and safe lifting on site

To retain all spilt fluids

Reducing service time



Stage 3A Engine



IVECO
1 Year Engine Warranty (Limited)

Specification

Performance

Alternator	Linz (AVR Controlled)	Three Phase Power (400V)	33kVA/ 26.4kW
Single Phase Power (110V)	N/A	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	11kVA/ 8.8kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	FPT (Iveco)	Fuel Consumption @ 75% Load (Litres/hour)	6.5
Type	FPT F32SM1F (Stage 3A)	Fuel Tank Capacity (Litres)	120
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	4	@ 100% Load	16
Power (HP)	43	@ 75% Load	18
Engine Speed (RPM)	1500	@ 50% Load	28
Cooling	Water	@ 25% Load	42
		CO ₂ Per Hour @ 75% Load	17.03kg
		Control Panel	Deepsea 7310 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 2025 mm	Width: 950 mm	Height: 1620 mm
Dry Weight (No Fuel): 950 kg	Wet Weight (Fuel Full): 1070 kg	

Dimensions (With road-tow kit)

Length: 3810 mm	Width: 1770 mm	Height: 2110 mm
Dry Weight (No Fuel): 1180 kg	Wet Weight (Fuel Full): 1300 kg	

Socket Configuration	3ph (400V)			1ph (230V)	
	63A	32A	16A	32A	16A
MGTP 33 SSF	1	1	-	3	2

Hard wire facility	3ph (400V)	1ph (230V)
MGTP 33 SSF	✓	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

