

MGTP 60 SSF

Ready to Rent 60kVA Diesel Generator



When looking for a robust, reliable, good quality 60kVA rental-friendly generator, our MGTP 60 SSF has everything the hire market requires.

Optional extras:



Road-tow Kit



GPS Telemetry Tracker

Features

60kVA 3ph AC Aux Power (400V)
Linz alternator
FPT (Iveco) diesel engine (Stage 3A)
HVO (Hydrotreated Vegetable Oil) fuel approved
Exclusive MHM-Gen engine protection shutdown system
3 way fuel valve
12V battery isolator switch
Emergency stop button
Variable RCD
ELR bypass switch (activated by key only)
Central lifting eye and fork pockets
Fully bunded base
Engine oil drain pump

Benefits

Plenty of power to meet the demands of medium to large generator hire
Heavy duty and proven reliability
World class performance and watercooled
Suitable to run off either diesel, HVO or a mixture of both fuels
In the case of low fuel, low oil pressure, high engine temp and battery charge failure
Easy connectivity to an external fuel tank
Reduces flat battery breakdowns
A must on any UK site
Flexible protection
Turn off the ELR to avoid nuisance tripping when powering electrical motors
Flexible and safe lifting on site
To retain all spilt fluids
Reducing service time



Stage 3A Engine



IVECO
1 Year Engine Warranty (Limited)

Specification

Performance

Alternator	Linz (AVR Controlled)	Three Phase Power (400V)	60kVA/ 48kW
Single Phase Power (110V)	N/A	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	20kVA/ 16kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	FPT (Iveco)	Fuel Consumption @ 75% Load (Litres/hour)	12
Type	N45 SM1F (Stage 3A)	Fuel Tank Capacity (Litres)	250
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	4	@ 100% Load	17
Power (HP)	83	@ 75% Load	21
Engine Speed (RPM)	1500	@ 50% Load	29
Cooling	Water	@ 25% Load	50
		CO ₂ Per Hour @ 75% Load	31.44kg
		Control Panel	Deepsea 7310 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 2160 mm	Width: 1070 mm	Height: 1760 mm
Dry Weight (No Fuel): 1450 kg	Wet Weight (Fuel Full): 1750 kg	

Dimensions (With road-tow kit)

Length: 4800 mm	Width: 1840 mm	Height: 2270 mm
Dry Weight (No Fuel): 1750 kg	Wet Weight (Fuel Full): 2050 kg	

Socket Configuration	3ph (400V)				1ph (230V)	
	125A	63A	32A	16A	32A	16A
MGTP 60 SSF	1	1	1	-	4	2

Hard wire facility	3ph (400V)	1ph (230V)
MGTP 60 SSF	✓	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

