

GW 300 ECO

300A Diesel Welder Gen

When looking for a robust, reliable, good quality 300A diesel welder, look no further than our GW 300 ECO.



Optional Trolley Chalwyn Valve Spark Arrestor Road-tow Remote Ωrſ Control extras: 300A MAN GENWELD **Benefits** Features DC welding range 50–300A Will burn up to a 6mm rod 8kVA AC generator power Plenty of power to run a variety (400/110V) of tools on site Kubota diesel engine World class performance (Stage 5) and watercooled Superior welding technology Unrivalled weld quality and performance Switchless power Can be used as a welder or generator or both simultaneously Fully bunded base To retain all spilt fluids Auto Idle & Eco mode Automatically saves noise, fuel & CO₂ emissions Kupola Stage **5**

6 @7m=63 H 23 Yes

Specification

Performance

| Welding (Amps DC) | 50-300 | Max Welding Rods (mm) |
|---------------------------|-------------|----------------------------|
| Duty Cycle (Amps) | Continuous | Noise Level LWA=88 dBa@ |
| Open Circuit Voltage (V) | 85 | Insulation Class |
| Single Phase Power (110V) | 3kVA/ 2.4kW | Mechanical Protection – IP |
| Three Phase Power (400V) | 8kVA/ 6.4kW | Remote Control Socket |
| | | |

Engine

| Lingine | | | |
|---------------------|----------------|--|----------|
| Make | Kubota | Cooling | Water |
| Туре | D722 (Stage 5) | Fuel Consumption @ 75% Load (Litres/hour |) 3 |
| Fuel | Diesel | Fuel Tank Capacity (Litres) | 37 |
| Number of Cylinders | 3 | Average Runtime (Hours) @ 75% Load | 12 |
| Power (HP) | 14 | CO2 Per Hour @ 75% Load | 7.86kg |
| Engine Speed (RPM) | 3000 | Starting System | Electric |
| | | | |

Dimensions (Machine only)

Engine

| Length: 1410 mm | Width: 566 mm | Hei | ight: 760 mm | | | |
|-------------------------------------|--------------------------------|--------------------------------|---------------------|--|--|--|
| Dry Weight (No Fuel): 348 kg | Wet Weight (Fuel Full): 383 kg | | | | | |
| Dimensions (With trolley kit) | | | | | | |
| Length: TBA mm | Width: TBA mm | Height: TBA mm | | | | |
| Dry Weight (No Fuel): TBA kg | | Wet Weight (Fuel Full): TBA kg | | | | |
| Dimensions (With road-tow kit) | | | | | | |
| Length: 2560 mm | Width: 1200 mm | Height: 1110 mm | | | | |
| Dry Weight (No Fuel): 393 kg | | Wet Weight (Fuel Full): 428 kg | | | | |
| | | | | | | |
| Socket | 3ph (400V) | 1ph (110V) | | | | |
| Configuration | 32A | 32A | 16A | | | |
| GW 300 ECO | 1 | 1 | 1 | | | |

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change



2 Year Engine

Warranty (Limited)