

GW 4/200-DC SINCRO

200A Petrol Welder Gen

Our 200A petrol welder is able to support the most common demands of the hire industry. The simple, robust and reliable design allows the operator to weld and use generator power at the same time.

Features

- 4kVA 110V AC generator power
- 4kVA 230V AC generator power
- DC Welding range 40–200A
- Honda petrol engine (Stage 5)
- Simple & robust design
- Complete with trolley kit

Benefits

- Enough to power 9" grinders
- Powerful 230V for many applications
- Will burn a 5mm rod
- Featuring low oil level shutdown
- Ideal for a rental environment
- Nice & easy manoeuvrability



Specification

Performance

Type	Sincro EW 200 DC	Single Phase Power (230V)	4kVA/ 3.2kW
Welding (Amps DC)	200	Max Welding Rods (mm)	5
Duty Cycle (Amps) @ 60% 170 @ 35% 200		Noise Level	LWA=97 dBa@7m=72
Open Circuit Voltage (V)	90	Insulation Class	H
Single Phase Power (110V)	4kVA/ 3.2kW	Mechanical Protection - IP	23
		Remote Control Socket	N/A

Engine

Make	Honda	Cooling	Air
Type	GX 390 (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)	2.7
Fuel	Petrol	Fuel Tank Capacity (Litres)	6.1
Number of Cylinders	1	Average Runtime (Hours) @ 75% Load	2.2
Power (HP)	13	CO ₂ Per Hour @ 75% Load	6.45kg
Engine Speed (RPM)	3000	Starting System	Recoil

Stage 5
Engine



POWERED by
HONDA
GX Engine 5 Year
Warranty (Limited)

Dimensions (Machine only)

Length: 820 mm	Width: 480 mm	Height: 620 mm
Dry Weight (No Fuel): 86 kg	Wet Weight (Fuel Full): 92 kg	

Dimensions (With trolley kit)

Length: 1120 mm	Width: 640 mm	Height: 765 mm
Dry Weight (No Fuel): 96 kg	Wet Weight (Fuel Full): 102 kg	

Socket Configuration	1ph (230V)	1ph (110V)
	16A	16A
GW 4/200-DC SINCRO	1	1

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy



GROUP
The Preferred Supplier

