

MG 20000 Cube (WELFARE)

Welfare Cabin Ready 20kVA Diesel Generator

When looking for robust, reliable, good quality 20kVA Welfare Ready Diesel Generator, look no further than our MG 20000 Cube (Welfare). **FUEL**

WELFARE

Optional







GPS Telemetry

20kVA (230V only)

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye and fork pockets

Exclusive MHM-Gen engine protection shutdown system

Extremely compact

Welfare cabin ready

Features Benefits

Plenty of power for most welfare cabin applications

Heavy duty and proven reliability

World class performance, 1500rpm

Suitable to run off either diesel, HVO or a mixture of both fuels

A must on any UK site

Flexible and safe lifting on site

In the case of low fuel, low oil pressure, and battery charge failure

Ideal when saving space is important

Easy fit, plug and play cabin installation







くいりっけっ

Specification

Performance

Alternator	Linz (AVR)
Single Phase Power (110V)	N/A
Single Phase Power (230V)	20kVA/ 16kW

Noise Level	LWA=88	dBa@7m=63
Insulation Class		Н
Mechanical Protection - IP		23

Make	Kubota
Туре	V2203 (Stage 3)
Fuel Diesel / HVO (HVO	= BS EN 15940:2016 Only)
Number of Cylinders	4
Power (HP)	TBA
Engine Speed (RPM)	1500
Cooling	Water

	Fuel Consumption @ 75% Load (Litres/hour)			ur) 4.2
	Fuel Tank Capacity (Litres)			120
Average Runtime (Hours)				
	@ 100% Load	22	@ 75% Load	29
	@ 50% Load	41	@ 25% Load	79
	CO2 Per Hour @ 75% Load 1°			11.01kg
	Control Panel Deepsea 3110 c/w two wire Auto Start/ Stop facility			

Dimensions (Machine only)

Length: 1500 mm	Width: 815 mm	Height: 1450 mm
Dry Weight (No Fuel): 736 kg		Wet Weight (Fuel Full): 856 kg

Socket Configuration	1ph (230V)			
	125A	63A	32A	16A
MG 20000 Cube (Welfare)	1	1	1	1
Hard wire facility	1ph (230V)			
MG 20000 Cube (Welfare)	V			

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com











