

MGKH-5 10000 Cube (WELFARE-LONGRUN)

Welfare Cabin Ready 9.8kVA Longrun Diesel Generator



When looking for robust, reliable, good quality 9.8kVA Welfare Ready Diesel Generator, look no further than our MGKH-5 10000 Cube (Welfare-Longrun). Specially featuring a 301 litre base fuel tank.

Optional extras:



Remote Start/Stop



Remote Start/Stop + timer control



GPS Telemetry Tracker

Features

- 9.8kVA (230V only) AC Aux Power
- Mecc Alte alternator
- Kohler diesel engine (Stage 5)
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Emergency stop button
- Central lifting eye
- Exclusive MHM-Gen engine protection shutdown system
- Extremely compact
- Extra large base fuel tank
- Welfare cabin ready

Benefits

- Plenty of power for most welfare cabin applications
- Heavy duty and proven reliability
- World class performance, 1500rpm and watercooled
- Suitable to run off either diesel, HVO or a mixture of both fuels
- A must on any UK site
- Flexible and safe lifting on site
- In the case of low fuel, low oil pressure, and battery charge failure
- Ideal when saving space is important
- To enable extremely long run time – 157 hours @ 75% load
- Easy fit, plug and play cabin installation

Water Cooled
Extra Super Silent

HVO
FUEL
APPROVED

WELFARE
CABIN
READY

1500
rpm



Stage 5
Engine



KOHLER
2 Year Engine
Warranty (Limited)

Specification

Performance

Alternator	Mecc Alte (AVR)	Noise Level	LWA=79 dBa@7m=54
Single Phase Power (110V)	N/A	Insulation Class	H
Single Phase Power (230V)	9.8kVA/ 7.8kW	Mechanical Protection - IP	23

Engine

Make	Kohler	Fuel Consumption @ 75% Load (Litres/hour)	1.9
Type	TBA (Stage 5)	Fuel Tank Capacity (Litres)	300
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	3	@ 100% Load	107
Power (HP)	13.7	@ 75% Load	157
Engine Speed (RPM)	1500	@ 50% Load	250
Cooling	Water	@ 25% Load	500
		CO ₂ Per Hour @ 75% Load	4.98kg
		Control Panel	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1240 mm	Width: 790 mm	Height: 1410 mm
Dry Weight (No Fuel): 465 kg		Wet Weight (Fuel Full): 708 kg

Socket Configuration

	1ph (230V)
	32A
MGKH-5 10000 Cube (Welfare-Longrun)	2

Hard wire facility

	1ph (230V)
MGKH-5 10000 Cube (Welfare-Longrun)	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy

