

GW 15/350 SSK

Water Cooled
Super Silent



350A Diesel Welder Gen

Our unique extra smooth DC power & extra large multi-voltage auxiliary power is a perfect solution for many power and welding applications whether it be on site or rental.



Multi Voltage
400V 230V 110V

Optional Extras All pictures are for illustration purposes only, actual machines supplied may differ in appearance and specification.



Features

- 15kVA Multi-voltage Aux power (400/230/110v)
- DC Welding range 30 - 350A
- Kubota Diesel Engine
- Chopper Technology
- Switchless AC and DC power

Benefits

- Hugely versatile with a great advantage in rental
- Will burn up to a 6mm rod
- World class performance, Watercooled
- Unrivalled weld quality & performance
- Can be used as a welder or generator or both simultaneously

Specifications

Performance

| | |
|---------------------------|-------------------------|
| Type | Linz + Permanent Magnet |
| Welding - amps D.C. | 30 - 350 |
| Open Circuit Voltage - V | 75 |
| Single Phase Power (110v) | 4kVA/ 3.2kW |
| Single Phase Power (230v) | 6kVA/ 4.8kW |
| Three Phase Power (400v) | 15kVA/ 12kW |

| | |
|------------------------------|-----|
| Max Welding Rods - mm | 6 |
| Noise Level LWA=88 dBa@7m=63 | |
| Insulation Class | H |
| Mechanical Protection - IP | 23 |
| Remote Control Socket | Yes |

Engine

| | |
|---------------------|--------|
| Make | Kubota |
| Type | D1105 |
| Fuel | Diesel |
| Number of Cylinders | 3 |
| Power - HP | 26 |

| | |
|------------------------------------|----------|
| Engine Speed - rpm | 3000 |
| Cooling | Water |
| Fuel Consumption - Litres/hour | 3 |
| Fuel Tank Capacity - litres | 32 |
| Average Runtime @ 75% Load (Hours) | 11 |
| Starting System | Electric |

Dimensions (Machine only)

| | |
|------------------|----------------|
| Length - 1410 mm | Width - 700 mm |
|------------------|----------------|

| | |
|-----------------|-----------------|
| Height - 835 mm | Weight - 390 Kg |
|-----------------|-----------------|

Dimensions (With trolley kit)

| | |
|------------------|----------------|
| Length - 1895 mm | Width - 940 mm |
|------------------|----------------|

| | |
|-----------------|-----------------|
| Height - 980 mm | Weight - 400 Kg |
|-----------------|-----------------|

Dimensions (With road-tow kit)

| | |
|------------------|-----------------|
| Length - 2500 mm | Width - 1160 mm |
|------------------|-----------------|

| | |
|------------------|-----------------|
| Height - 1130 mm | Weight - 520 Kg |
|------------------|-----------------|

Socket Configuration

| | 3ph (400V) | | 1ph (230V) | | 1ph (110V) | |
|----------------------|------------|-----|------------|-----|------------|-----|
| | 32A | 16A | 32A | 16A | 32A | 16A |
| GW 15/350 SSK | 1 | - | 1 | - | 1 | - |

Tel +44 (0)1639 777 009

E-mail sales@mhplant.com

Designed in the UK

Built in Italy



www.mhplant.com