

GW 6/200 SSK

Water Cooled
Super
Silent

200A Diesel Welder Gen

This superb design is the workhorse diesel welder/ gen in our range offering a great portable solution for many power and welding applications whether it be on site or rental.



Optional Extras All pictures are for illustration purposes only, actual machines supplied may differ in appearance and specification.



Road-tow
Kit



Chalwyn
Valve



Spark
Arrestor



Remote
Control

Features

- 6kVA (230v/110v) AC Aux Power
- DC Welding range 40 - 210A
- Kubota diesel engine
- Complete with trolley kit
- Switchless AC and DC power

Benefits

- Plenty of power to run a variety of tools on site
- Will burn up to a 5mm rod
- World class performance & Water cooled
- Nice and easy manoeuvrability
- Can be used as a welder or generator or both simultaneously

Specifications

Performance

| | |
|---------------------------|-------------------------|
| Type | Linz + Permanent Magnet |
| Welding - amps D.C. | 30 - 200 |
| Open Circuit Voltage - V | 80 |
| Single Phase Power (110v) | 6kVA/ 4.8kW |
| Single Phase Power (230v) | 6kVA/ 4.8kW |

| | |
|------------------------------|-----|
| Max Welding Rods - mm | 5 |
| Noise Level LWA=89 dBa@7m=64 | |
| Insulation Class | H |
| Mechanical Protection - IP | 23 |
| Remote Control Socket | Yes |

Engine

| | |
|---------------------|--------|
| Make | Kubota |
| Type | Z 482 |
| Fuel | Diesel |
| Number of Cylinders | 2 |
| Power - HP | 10 |

| | |
|------------------------------------|----------|
| Engine Speed - rpm | 3000 |
| Cooling | Water |
| Fuel Consumption - Litres/hour | 1.8 |
| Fuel Tank Capacity - litres | 40 |
| Average Runtime @ 75% Load (Hours) | 22 |
| Starting System | Electric |

Dimensions (Machine only)

| | |
|------------------|----------------|
| Length - 1280 mm | Width - 710 mm |
|------------------|----------------|

| | |
|-----------------|-----------------|
| Height - 880 mm | Weight - 240 Kg |
|-----------------|-----------------|

Dimensions (With trolley kit)

| | |
|------------------|----------------|
| Length - 1740 mm | Width - 940 mm |
|------------------|----------------|

| | |
|------------------|-----------------|
| Height - 1005 mm | Weight - 265 Kg |
|------------------|-----------------|

Dimensions (With road-tow kit)

| | |
|------------------|-----------------|
| Length - 2450 mm | Width - 1150 mm |
|------------------|-----------------|

| | |
|------------------|-----------------|
| Height - 1040 mm | Weight - 370 Kg |
|------------------|-----------------|

Socket Configuration

| | 3ph (400V) | | 1ph (230V) | | 1ph (110V) | |
|---------------------|------------|-----|------------|-----|------------|-----|
| | 32A | 16A | 32A | 16A | 32A | 16A |
| GW 6/200 SSK | - | - | 1 | 1 | 1 | 1 |

